

**POTVRDA O TIPNOM ODOBRENJU**
TYPE APPROVAL CERTIFICATE

Br /No 03-001292/030962

Potvrđuje se da je ovaj proizvod, u skladu s Pravilima za klasifikaciju brodova, Dio 1. - Opći propisi, Odjeljak 3. - Tipno odobrenje proizvoda, odobren za ugradnju na brodove i postrojenja pod nadzorom Hrvatskog registra brodova.
This is to certify that this product, on the basis of the Rules for the classification of ships, Part 1 - General requirements, Chapter 3 - Type approval of products, is approved for use on board ships and installations under supervision of the Croatian Register of Shipping.

TIP I OPIS PROIZVODA:
TYPE AND DESCRIPTION OF PRODUCT:

BRODSKI ENERGETSKI I KONTROLNI KABEL BEZHALOGENI I VATROOTPORN
SHIPBOARD POWER AND CONTROL CABLE HALOGEN FREE AND FIRE RESISTANT
LKM-FRHF/LKSM-FRHF/LKAM-FRHF/LKSM-EMC-FRHF 0,6/1 (1,2) kV

PROIZVOĐAČ:
MANUFACTURER:

HELKAMA BICA Oy
Lakimiehenkatu 4
FIN-20780 Kaarina
FINLAND

PROIZVOD UDOVOLJAVA SLIJEDEĆIM PRAVILIMA/PROPISIMA:
THE PRODUCT MEETS FOLLOWING RULES/REGULATIONS:

HRB PRAVILA ZA KLASIFIKACIJU BRODOVA: DIO 12 - ELEKTRIČNA OPREMA
CRS RULES FOR THE CLASSIFICATION OF SHIPS: PART 12 - ELECTRICAL EQUIPMENT

Helkama specification: HBKQ 9 spec.23, 24, 60 and 84

Technical specification:

Design standard: IEC 60092-353 (3rd ed 2011-08),
Single and multicore non-radial field power cable 0,6/1 kV

Other standards:

- testing: IEC 60092-350 (3rd Ed. 2008-02), General constructions and testing requirements
- insulation: IEC 60092-351 (3rd ed. 2004-04), Insulating materials
- sheathing: IEC 60092-359 (1.2nd ed. 1999-08)
Sheathing materials for shipboard power and telecommunication cables

DETALJI O PROIZVODU I UVJETIMA CERTIFIKACIJE DANI SU NA POLEDINI.
FURTHER DETAILS OF THE PRODUCT AND CONDITIONS FOR CERTIFICATION ARE GIVEN OVERLEAF.

ODOBRENJE VRIJEDI DO: 2016-02-10
APPROVAL IS VALID UNTIL:

Mjesto i datum: Split, 2012-02-10
Place and date:




Goran Begović, dipl.ing.

NAPOMENA: Ova potvrda nije valjana ako se proizvod ili način njegove proizvodnje promijenio u odnosu na tipno ispitani proizvod. Proizvođač treba obavijestiti Hrvatski registar brodova o bilo kojoj izmjeni na proizvodu kako bi ishodio valjanu potvrdu.
NOTE: This certificate is not valid for equipment, the design or manufacture of which has been varied or modified from the specimen tested. The manufacturer should notify Croatian Register of Shipping of any modification or changes to the product in order to obtain a valid certificate.

PODROBNIJI OPIS PROIZVODA:*DETAILED PRODUCT DESCRIPTION:*

Multi core power and control cable for fixed marine installations. Flame retardant, fire resistant, low smoke, halogen free. XLPE insulated, 0.6/1 kV (1.2 kV)

The LKSM-EMC-FRHF is designed with enhanced Electromagnetic compatibility (EMC) characteristics.

LKM-FRHF – Unscreened

LKSM-FRHF – Cu-braid screened

LKAM-FRHF – Al-polyester- tape screened

LKSM-EMC-FRHF – Cu-tape & Cu-braid screened

Cable Type	No of Cores	Cross Sect area [mm ²]
LKM-FRHF, LKSM-FRHF	1	1.0, 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300
LKM-FRHF, LKSM-FRHF	2	1.0, 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95
LKM-FRHF, LKSM-FRHF	3	1.0, 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240
LKM-FRHF, LKSM-FRHF	4	1.0, 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150
LKM-FRHF	5	1.0, 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95
LKSM-FRHF	5	1.0, 1.5, 2.5, 4, 6, 10, 16, 25, 60, 70
LKAM-FRHF	2, 3, 4, 5	1.0, 1.5, 2.5
LKM-FRHF, LKSM-FRHF, LKAM-FRHF	7,10,12,14,16,19,24,27,37	1.0, 1.5, 2.5
LKSM-EMC-FRHF	1	1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300
LKSM-EMC-FRHF	2	1.5, 2.5, 4, 6, 10, 16, 25, 35
LKSM-EMC-FRHF	3	1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240
LKSM-EMC-FRHF	4	1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120
LKSM-EMC-FRHF	5	1.5, 2.5, 4, 6, 10, 16, 25
LKSM-EMC-FRHF	7,10,12,14,16,19,24,27,37	1.5, 2.5

PODRUČJE PRIMJENE / POSEBNI GRANIČNI UVJETI:*APPLICATION / LIMITATIONS:*

Fiksna ugradnja na pomorskim brodovima, odobalnim objektima i industriji.

Fixed installation in marine, offshore and industrial use.

DOKUMENTACIJA ZA TIPNO ODOBRENJE:*TYPE APPROVAL DOCUMENTATION:*

Helkama Application on LKM-FRHF / LKSM-FRHF / LKAM-FRHF & LKSM-EMC	2012-01-27
Helkama LKM-FRHF 0.6/1 (1.2 kV) Cable Data Sheet Specification HBKQ 9. Spec 23 incl. App 1, 2 & 3	2011-06-30
Helkama LKSM-FRHF 0.6/1 (1.2 kV) Cable Data Sheet Specification HBKQ 9. Spec 24 incl. App 1, 2 & 3	2011-07-01
Helkama LKAM-FRHF 0.6/1 (1.2 kV) Cable Data Sheet Specification HBKQ 9. Spec 60 incl. App 1 & 2	2011-06-28
Helkama LKSM-EMC-FRHF 0.6/1 kV Cable Data Sheet Specification HBKQ 9 Spec 84 with App 1, 2 & 3	2011-06-16

Izvještaj o ispitivanju/ test report:

LKSM-FRHF/ TT doc_h/S TT_1_5 sm; LKM-FRHF/67184 Tt_1_5; LKAMFR-HF/LKAM-FRHF 3x 1,5_TTI

OZNAČAVANJE PROIZVODA:*MARKING OF PRODUCT:*

LOT ##### LKM-FRHF (or LKSM-FRHF) “number of core” x “size of conductor” mm² 0,6/1 kV + 90°C IEC 60092-353, 60331-21 (or 60331-1 [90]), 60332-3-22 HELKAMA “month-year” and “length marking”.

LOT ##### LKAM-FRHF “number of core” x “size of conductor” mm² 0,6/1 kV + 90°C IEC 60092-353, 60332-3-22, 60331 HELKAMA “month-year” and “length marking”.

LOT ##### LKSM-EMC-FRHF “number of core” x “size of conductor” mm² 0,6/1 kV + 90°C IEC 60092-353, 60331-2 [120] (or 60331-1 [120]), 60332-3-22 HELKAMA “month-year” and “length marking”.

Note: Cable with conductor of IEC 60228 class 5 shall be marked on the sheath with “cl. 5”

UVJETI ZA CERTIFIKACIJU:*CONDITIONS FOR CERTIFICATION:*

NON

Raščlana

Zamjenjuje potvrdu

12.05.01

-